



Front ITO Film-0.188mm  
 Back ITO Glass-1.8mm  
 Thick: 2.3±0.15

- Note:
1. Typical Film to Glass
  2. Operating Voltage: ±10V
  3. Operating Temperature: -30°C ~ +85°C
  4. Storage Temperature: -30°C ~ +70°C
  - 4.1 Life Time: 1,000,000 times
  5. Contact Material: s-Pt/C
  6. Response Time: <math>t\_{10ms}</math>
  7. Lifetime: <math>t\_{1.5%}</math>
  8. Transmittance: > 92%
  9. Surface Hardness: (diamond) > 3H
  10. Operation Force: > 100g

11. Resistance: UR <math>< 20k\Omega</math>, LR <math>< 20k\Omega</math>, LL <math>< 20k\Omega</math>, UL <math>< 20k\Omega</math>  
 UR <math>< 20k\Omega</math>, LR <math>< 20k\Omega</math>, LL <math>< 20k\Omega</math>, UL <math>< 20k\Omega</math>  
 UR <math>< 20k\Omega</math>, LR <math>< 20k\Omega</math>, LL <math>< 20k\Omega</math>, UL <math>< 20k\Omega</math>

TOLERANCES

QUALITY	OTHERWISE STATED	DEFAULT	ANGLES	AS SHOWN
±0.13mm	±0.13mm	±0.13mm	±0.13mm	±0.13mm
±0.05mm	±0.05mm	±0.05mm	±0.05mm	±0.05mm
±0.02mm	±0.02mm	±0.02mm	±0.02mm	±0.02mm
±0.01mm	±0.01mm	±0.01mm	±0.01mm	±0.01mm
±0.005mm	±0.005mm	±0.005mm	±0.005mm	±0.005mm
±0.002mm	±0.002mm	±0.002mm	±0.002mm	±0.002mm
±0.001mm	±0.001mm	±0.001mm	±0.001mm	±0.001mm
±0.0005mm	±0.0005mm	±0.0005mm	±0.0005mm	±0.0005mm
±0.0002mm	±0.0002mm	±0.0002mm	±0.0002mm	±0.0002mm
±0.0001mm	±0.0001mm	±0.0001mm	±0.0001mm	±0.0001mm

GreenTouch Technology Co., Ltd

Model No.	GT-10.4-1	Size	10.4"	Resolution	480
Color	White	Material	ITO/Glass	Temp	55
Weight	100g	Thickness	2.3mm	Viewing Angle	170
Response Time	10ms	Operating Voltage	±10V	Operating Temperature	-30°C ~ +85°C
Storage Temperature	-30°C ~ +70°C	Life Time	1,000,000 times	Contact Material	s-Pt/C
Response Time	<math>t_{10ms}</math>	Lifetime	<math>t_{1.5%}</math>	Transmittance	> 92%
Surface Hardness	(diamond) > 3H	Operation Force	> 100g		