



- Notes:
- 1.Type:Film to Glass
 - 2.Operating Voltage:<10v
 - 3.Operation Temperature:20℃~65℃
 - 4.Life Time:1,000,000 times
 - 5.Connect Material:FPC
 - 6.Response Time:<10ms
 - 7.Linearity:<1.5%
 - 8.Transmittance ≥75%
 - 9.Surface Hardness:3H(pencil)
 - 10.Operation force:50g~150g

- 11.Resistance:50Ω <PIN1,PIN2 <250Ω
50Ω <PIN2,PIN4 <250Ω
50Ω <PIN4,PIN5 <250Ω
50Ω <PIN5,PIN1 <250Ω

TOLERANCES (UNLESS OTHERWISE STATED)		GreenTouch Technology Co.,Ltd	
DECIMALS	ANGLES ±0.05°	Model No:	GT-08-173-1
>2500MM	±2.50MM	Size	17.3"
1000~X <2500MM	±1.50MM	Sheet	04F
1200~X <1000MM	±0.50MM	Unit	mm
800~X <1200MM	±0.30MM	Date	2015.5.5
400~X <800MM	±0.40MM	Design	PPB
120~X <400MM	±0.30MM	Check	010-PS
30~X <120MM	±0.20MM	Release	02B
<30MM	±0.10MM	Date	2015.5.5
		Page	1/1
		Version	A0